# BREAKER

## KV 16

**Breaker respects all safety CE norms and limits on noise, vibration level and defence against accidental starting**

- *Anti vibration handles according to the newest CE regulations allow operators comfort and safety*
- *Can work at flow 20 or 30 L/min*
- *Only one dynamic seal and few moving parts to assure maximum reliability and a unbeatable operative longevity*
- *High tolerance to back pressure allows to use it with very long oil hoses*
- *No vulnerable plastic parts -Slim tool profile without side rods or sharp angles assures maximum ergonomics*
- *Available with special percussion heads configured to dig in electric earthing pickets or small poles*



**KV16** hydraulic breaker Kg16 with “T type” anti vibration handles suspended on springs, it is “operator friendly” and its use is ideal in general demolition works of concrete and asphalt cutting. **KV16** gives the best compromise between high power and manoeuvrability, can be powered by power packs or by the hydraulic circuit of mini excavators, trucks or other machines with sufficient hydraulic circuit. The hydraulic functioning assures quietness, productivity, fuel economy united with the excellent transportability of the group power pack/breaker eliminating the typical problems of transport and movements of the bulky air compressors and pneumatic breakers.

| **TECHNICAL** CHARACTERISTICS | **KV 16** |
|---|---|
| **Weight (kg)** | 16 |
| **Dimension LxP (cm)** | 60x45 |
| **Tool bitz size mm** | 22x82 std (7/8”x3$^{3/4”}$) |
| **Flow L/min** | 20-30 |
| **Ideal flow L/min** | 20 |
| **Pressure Bar** | 140 |
| **Blow frequency** | 1300-1500 |
| **Impact energy** | 5,5 KGM |
| **Handle type** | “T” anti vibration |



DOA Hydraulic Tools

22066 Mariano Comense (CO) - ITALY - Via Sant’Agostino 158
Tel. (+39) 031 792 040 - www.doa-srl.com - info@doa.it